



INSTITUTIONAL HOLLOW KINGPIN MODELS



Top Lock Brake Add [TL] at end of model. Swivel radius 4-3/8".

Tread Lock Brake Add [TB] at end of model.

Total Lock Brake Change 3rd digit to "T". Swivel radius 4-3/8". Example: PGT30400ZN-HDR01(KK).

Hollow Kingpin Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Thread Guard	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection	
3"	1-1/4"	Hard Rubber	Plain	None	210	4-1/8"	2-7/8"	PGS30400ZN-HDR01(KK)	400	
	1-1/4"	Polyolefin	Plain	None	250	4-1/8"	2-7/8"	PGS30400ZN-PCD01(KK)	400	
	1-1/4"	Soft Rubber	Plain	None	150	4-1/8"	2-7/8"	PGS30400ZN-SFR01(KK)	400	
	1-1/4"	TPR	Nylon	None	210	4-1/8"	2-7/8"	PGS30400ZN-TPR11(GG)	400	
	1-1/4"	TPR	Ball	None	210	4-1/8"	2-7/8"	PGS30400ZN-TPR21(GG)	400	
	1-1/4"	TPR	Ball	Precision	Full	210	4-1/8"	2-7/8"	PGS30400ZN-TPR33(GG)	400
	1-1/4"	Urethane (Blue)	Ball	None	250	4-1/8"	2-7/8"	PGS30400ZN-TPU21(BG)	400	
	1-1/4"	Urethane (Grey)	Ball	None	250	4-1/8"	2-7/8"	PGS30400ZN-TPU21(GG)	400	
3-1/2"	1-1/4"	Hard Rubber	Plain	None	50	4-5/8"	3"	PGS35400ZN-HDR01(KK)	400	
	1-1/4"	Soft Rubber	Plain	None	150	4-5/8"	3"	PGS35400ZN-SFR01(KK)	400	
	1-1/4"	TPR	Nylon	None	250	4-5/8"	3"	PGS35400ZN-TPR11(GG)	400	
	1-1/4"	TPR	Ball	Partial	250	4-5/8"	3"	PGS35400ZN-TPR22(GG)	400	
	1-1/4"	Mono Tech	Ball	None	250	4-5/8"	3"	PGS35400ZN-MNT01(GG)	400	
	1-1/4"	Mono Tech	Ball	None	250	4-5/8"	3"	PGS35400ZN-MNT21(GG)	400	
	1-1/4"	Mono Tech	Ball	Full	250	4-5/8"	3"	PGS35400ZN-MNT23(GG)	400	
	1-1/4"	Urethane (Blue)	Ball	Partial	275	4-5/8"	3"	PGS35400ZN-TPU22(BG)	400	
1-1/4"	Urethane (Grey)	Ball	Partial	275	4-5/8"	3"	PGS35400ZN-TPU22(GG)	400		
4"	1-1/4"	Hard Rubber	Plain	None	255	5-1/8"	3-3/8"	PGS40400ZN-HDR01(KK)	400	
	1-1/4"	Polyolefin	Plain	None	275	5-1/8"	3-3/8"	PGS40400ZN-PCD01(KK)	400	
	1-1/4"	Soft Rubber	Plain	None	165	5-1/8"	3-3/8"	PGS40400ZN-SFR01(KK)	400	
	1-1/4"	TPR	Nylon	None	260	5-1/8"	3-3/8"	PGS40400ZN-TPR11(GG)	400	
	1-1/4"	TPR	Ball	Partial*	260	5-1/8"	3-3/8"	PGS40400ZN-TPR22(GG)	400	
	1-1/4"	TPR	Ball	Precision	Full	260	5-1/8"	3-3/8"	PGS40400ZN-TPR33(GG)	400
	1-1/4"	Mono Tech	Ball	None	300	5-1/8"	3-3/8"	PGS40400ZN-MNT01(GG)	400	
	1-1/4"	Mono Tech	Ball	None	300	5-1/8"	3-3/8"	PGS40400ZN-MNT21(GG)	400	
1-1/4"	Mono Tech	Ball	Full	300	5-1/8"	3-3/8"	PGS40400ZN-MNT23(GG)	400		
1-1/4"	Urethane (Blue)	Ball	Partial*	300	5-1/8"	3-3/8"	PGS40400ZN-TPU22(BG)	400		
1-1/4"	Urethane (Grey)	Ball	Partial*	300	5-1/8"	3-3/8"	PGS40400ZN-TPU22(GG)	400		
5"	1-1/4"	Hard Rubber	Plain	None	280	6-1/8"	4-1/4"	PGS50400ZN-HDR01(KK)	400	
	1-1/4"	Polyolefin	Plain	None	300	6-1/8"	4-1/4"	PGS50400ZN-PCD01(KK)	400	
	1-1/4"	Soft Rubber	Plain	None	200	6-1/8"	4-1/4"	PGS50400ZN-SFR01(KK)	400	
	1-1/4"	TPR	Nylon	None	280	6-1/8"	4-1/4"	PGS50400ZN-TPR11(GG)	400	
	1-1/4"	TPR	Ball	Partial*	280	6-1/8"	4-1/4"	PGS50400ZN-TPR22(GG)	400	
	1-1/4"	TPR	Ball	Precision	Full	280	6-1/8"	4-1/4"	PGS50400ZN-TPR33(GG)	400
	1-1/4"	Urethane (Blue)	Ball	Partial*	315	6-1/8"	4-1/4"	PGS50400ZN-TPU22(BG)	400	
	1-1/4"	Urethane (Grey)	Ball	Partial*	315	6-1/8"	4-1/4"	PGS50400ZN-TPU22(GG)	400	
1-1/4"	Mono Tech	Ball	None	325	6-1/8"	4-1/4"	PGS50400ZN-MNT01(GG)	400		
1-1/4"	Mono Tech	Ball	None	325	6-1/8"	4-1/4"	PGS50400ZN-MNT21(GG)	400		
1-1/4"	Mono Tech	Ball	Full	325	6-1/8"	4-1/4"	PGS50400ZN-MNT23(GG)	400		

*To order 4" and 5" TPR ball bearing wheels less thread guard change 15th digit to "1" (Example PGS40400ZN-TPR21(KK)).

Standard hollow king pin size is 1/2". To use with 3/8" bolt order [Bushing 3/8 GT].

