



Omega



Features

- Fully heat treated
- Dual ball bearing raceways
- High luster chrome finish
- Matching chrome thread guards
- Precision ball bearings for excellent rollability
- Choice of new vipor wheel (85-90A) or soft neoprene rubber (50-60A) durometer

Applications

- Medical Equipment
- Electronic Equipment
- Seating

Options

Brakes: Tread brake uniformly integrated into body design for smooth look and ease of activation 3" neoprene model only.

Bolt-In Stems:

A variety of stems can be attached to the kingpinless fastening #403 providing the ultimate in versatility. Contact factory for bolt-in stem part numbers.



Wheel Selection




Hollow Kingpin Models (7/16": Recommended mounting bolt 3/8" diameter - 16 x 1/2" minimum)

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
3"	15/16"	Neoprene	Precision	110 lbs	3-7/8"	2-7/8"	PCM30403BC-NPR	403
	15/16"	Vipor	Precision	120 lbs	3-7/8"	2-7/8"	PCM30403BC-VPR33(CK)	403



Grip Ring Stem Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
2"	15/16"	Neoprene	Precision	75 lbs	2-3/4"	2"	PCM20201BC-NPR	201
3"	15/16"	Neoprene	Precision	110 lbs	3-7/8"	2-7/8"	PCM30____BC-NPR	222, 223, 211
	15/16"	Vipor	Precision	120 lbs	3-7/8"	2-7/8"	PCM30____BC-VPR33(CK)	222, 223, 211



To order include fastener code. Example: PCM20201ZN-NPR

