

Z Series Nylon



Features

- Strong durable glass filled nylon body
- Sleek stylish design
- Sealed precision wheel bearings
- Pin-less Total Lock and Direction Lock brake design

Applications

- Medical Equipment
- Foodservice Equipment
- Store Fixtures
- Utility Carts

Options


Brake: Total Lock, locks wheel and swivel (all models). Direction lock locks just swivel (swivel plate models only).
Stainless Steel Components
Contact factory for pricing and minimum orders.



Threaded Stem

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
4"	1-1/4"	TPR	Sealed Precision	260 lbs	5-3/8"	3-1/2"	PZS40__GR-TPR33(GG)	741, 748
5"	1-1/4"	TPR	Sealed Precision	290 lbs	6-3/8"	4-1/16"	PZS50__GR-TPR33(GG)	741, 748

To order Total Lock Brake model change 3rd digit to "T". Swivel radius is 4-9/16".
Example: PZT40741GR-TPR33(GG)



To order include fastener code.
Example: PZS40741GR-TPR33(GG)



Grip Ring Stem Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
4"	1-1/4"	TPR	Sealed Precision	260 lbs	5-3/8"	3-1/2"	PZS40291GR-TPR33(GG)	291
5"	1-1/4"	TPR	Sealed Precision	290 lbs	6-3/8"	4-1/16"	PZS50291GR-TPR33(GG)	291

To order Total Lock Brake model change 3rd digit to "T". Swivel radius is 4-9/16".
Example: PZT40291GR-TPR33(GG)



Swivel Top Plate Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
4"	1-1/4"	TPR	Sealed Precision	260 lbs	5-7/16"	3-1/2"	PZS40120GR-TPR33(GG)	120
5"	1-1/4"	TPR	Sealed Precision	290 lbs	6-7/16"	4-1/16"	PZS50120GR-TPR33(GG)	120

To order Total Lock Brake model change 3rd digit to "T". Swivel radius is 4-9/16".
Example: PZT40120GR-TPR33(GG)

To order Direction Lock Brake model change 3rd digit to "D". Swivel radius is 4-9/16".
Example: PZD40120GR-TPR33(GG)

