

# Bassick Honcho OS/OR

1-800-215-8220



## Features

- Heavy, stamped leg construction
- Heat treated, dual ball bearing raceways
- Wraparound welded legs are located directly under the main support swivel bearings for added strength
- Sealed upper and lower ball races
- Yellow dichromate finish for added corrosion resistance

## Applications

- Power Towed Application
- Terminal Trucks
- High Abuse Applications

## Options

**Swivel Lock:** 4 position swivel lock. To order, add [-SLB] to end of model.

## Wheel Selection



Urethane on Aluminum



Steel



**Swivel Lock**  
Add [-SLB] at end of model.



## OS Swivel Top Plate Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number
5"	2"	Urethane on Aluminum	Sealed Roller	1500	6-1/2"	4"	COS50158YZ-UOA81(BG)
	2"	Steel	Roller	1750	6-1/2"	4"	COS50158YZ-STL51(GG)
6"	2"	Urethane on Aluminum	Sealed Roller	1500	7-1/2"	4-3/4"	COS60158YZ-UOA81(BG)
	2"	Steel	Roller	1750	7-1/2"	4-3/4"	COS60158YZ-STL51(GG)
8"	2"	Urethane on Aluminum	Sealed Roller	1500	9-1/2"	6"	COS80158YZ-UOA81(BG)
	2"	Steel	Roller	1750	9-1/2"	6"	COS80158YZ-STL51(GG)

## OR Rigid Top Plate Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number
5"	2"	Urethane on Aluminum	Sealed Roller	1500	6-1/2"	N/A	COR50158YZ-UOA81(BG)
	2"	Steel	Roller	1750	6-1/2"	N/A	COR50158YZ-STL51(GG)
6"	2"	Urethane on Aluminum	Sealed Roller	1500	7-1/2"	N/A	COR60158YZ-UOA81(BG)
	2"	Steel	Roller	1750	7-1/2"	N/A	COR60158YZ-STL51(GG)
8"	2"	Urethane on Aluminum	Sealed Roller	1500	9-1/2"	N/A	COR80158YZ-UOA81(BG)
	2"	Steel	Roller	1750	9-1/2"	N/A	COR80158YZ-STL51(GG)

▲ 158

