

Z Series Plastic Institutional

1-800-215-8220



Features

- Dual ball bearing raceway construction
- Labyrinth raceway seal to keep out moisture and debris
- Strong durable glass filled nylon body
- Sleek stylish design
- Sealed precision wheel bearing
- Stainless steel brake spring

Applications

- Medical Equipment
- Computer Carts
- Utility Carts
- Store Fixtures
- Foodservice Equipment

Options

Brakes: Total Lock locks wheel and swivel, direction lock locks just the swivel.


Stainless Steel Components: Contact factory

Threaded Stem Swivel Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
4"	1-1/4"	TPR	Sealed Precision	260 lbs	5-3/8"	3-1/2"	PZS40 GR-TPR33(GG)	741, 748
5"	1-1/4"	TPR	Sealed Precision	280 lbs	6-3/8"	4-1/16"	PZS50 GR-TPR33(GG)	741, 748
6"	1-1/4"	TPR	Sealed Precision	300 lbs.	7-3/8"	4-3/4"	PZS60 GR-TPR33(GG)	741, 748

Threaded Stem Total Lock Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
4"	1-1/4"	TPR	Sealed Precision	260 lbs	5-3/8"	4-1/2"	PZT40 GR-TPR33(GG)	741, 748
5"	1-1/4"	TPR	Sealed Precision	280 lbs	6-3/8"	4-1/2"	PZT50 GR-TPR33(GG)	741, 748
6"	1-1/4"	TPR	Sealed Precision	300 lbs.	7-3/8"	5-1/16"	PZT60 GR-TPR33(GG)	741, 748




To order include fastener code.
Example: PZS40741GR-TPR33(GG)

Grip Ring Stem Swivel Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
4"	1-1/4"	TPR	Sealed Precision	260 lbs	5-3/8"	3-1/2"	PZS40291GR-TPR33(GG)	291
5"	1-1/4"	TPR	Sealed Precision	280 lbs	6-3/8"	4-1/16"	PZS50291GR-TPR33(GG)	291
6"	1-1/4"	TPR	Sealed Precision	300 lbs.	7-3/8"	4-3/4"	PZS60291GR-TPR33(GG)	291

Grip Ring Stem Total Lock Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
4"	1-1/4"	TPR	Sealed Precision	260 lbs	5-3/8"	4-1/2"	PZT40291GR-TPR33(GG)	291
5"	1-1/4"	TPR	Sealed Precision	280 lbs	6-3/8"	4-1/2"	PZT50291GR-TPR33(GG)	291
6"	1-1/4"	TPR	Sealed Precision	300 lbs.	7-3/8"	5-1/16"	PZT60291GR-TPR33(GG)	291



Swivel Top Plate Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
4"	1-1/4"	TPR	Sealed Precision	260 lbs	5-7/16"	3-1/2"	PZS40120GR-TPR33(GG)	120
5"	1-1/4"	TPR	Sealed Precision	280 lbs	6-7/16"	4-1/16"	PZS50120GR-TPR33(GG)	120
6"	1-1/4"	TPR	Sealed Precision	300 lbs.	7-7/16"	4-3/4"	PZS60120GR-TPR33(GG)	120

Swivel Top Plate Total Lock Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
4"	1-1/4"	TPR	Sealed Precision	260 lbs	5-7/16"	4-1/2"	PZT40120GR-TPR33(GG)	120
5"	1-1/4"	TPR	Sealed Precision	280 lbs	6-7/16"	4-1/2"	PZT50120GR-TPR33(GG)	120
6"	1-1/4"	TPR	Sealed Precision	300 lbs.	7-7/16"	5-1/16"	PZT60120GR-TPR33(GG)	120

Swivel Top Plate Direction Lock Models

Wheel Dia.	Tread Width	Tread Type	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
5"	1-1/4"	TPR	Sealed Precision	280 lbs	6-7/16"	4-1/2"	PZD50120GR-TPR33(GG)	120
6"	1-1/4"	TPR	Sealed Precision	300 lbs.	7-7/16"	5-1/16"	PZD60120GR-TPR33(GG)	120

